

Clear Magic

Tier Haarpflege- Festigungsspray
Identifikations-Nr.: CPID: 605491-47
Berufliche Verwendung



284g
UN1950



Extrem entzündbares Aerosol. Behälter steht unter Druck: kann bei Erwärmung bersten. Gesundheitsschädlich bei Verschlucken, Hautkontakt oder Einatmen. Kann vermutlich Krebs erzeugen. Längere Exposition kann chronische Auswirkungen haben.

Darf nicht in die Hände von Kindern gelangen. Von Hitze/ Funken/ offener Flamme/ heißen Oberflächen fernhalten - Nicht rauchen. Behälter steht unter Druck: Nicht durchstechen oder verbrennen, auch nicht nach der Verwendung. Gas/ Dampf/ Aerosol nicht einatmen. Bei Hautreizung: Ärztlichen Rat einholen/ ärztliche Hilfe hinzuziehen. Vor Sonnenbestrahlung schützen nicht Temperaturen von mehr als 50°C aussetzen.

Inverkehrbringer:
Ruegruet Service GmbH, Grüt 7, 6276 Hohenrain / Tel. 041 911 25 25

MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product number 1000002937
Material name 10 OZ 12PK CLEAR MAGIC
Revision date 11-11-2013
Company information Stone Manufacturing & Supply Company, Inc.
1212 Kansas Ave
Kansas City , MO 64127 United States
Company phone 1-816-231-4020
Emergency telephone US 1-866-836-8855
Emergency telephone outside US 1-952-852-4646
Version # 02
Supersedes date 11-06-2013

2. Hazards Identification

Emergency overview DANGER

Flammable. CONTENTS UNDER PRESSURE.
Aerosol. Pressurized container may explode when exposed to heat or flame. May cause flash fire or explosion.

Will be easily ignited by heat, spark or flames. Harmful in contact with eyes. Cancer hazard. Irritating to skin. Irritating to respiratory system. Prolonged exposure may cause chronic effects.

OSHA regulatory status This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).
Potential health effects
Routes of exposure Inhalation. Ingestion. Skin contact. Eye contact.
Eyes Eye contact may result in corneal injury. Contact with eyes may cause irritation.
Skin Irritating to skin. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
Inhalation May cause cancer by inhalation. Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Irritating to respiratory system. Prolonged inhalation may be harmful.
Ingestion Exposure by ingestion of an aerosol is unlikely. Components of the product may be absorbed into the body by ingestion.
Target organs Cardiac. Central nervous system. Kidneys. Liver. Lungs. Respiratory system.
Chronic effects Shortness of breath. Conjunctiva. Edema. Jaundice. Liver injury may occur. Kidney injury may occur. May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion and blurred vision) and/or damage. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. May cause delayed lung injury.
Signs and symptoms Discomfort in the chest. Shortness of breath. Corneal damage. Narcosis. Decrease in motor functions. Behavioral changes. Coughing. Edema. Liver enlargement. Jaundice. Conjunctivitis. Proteinuria. Irritating to mouth, throat, and stomach. Skin irritation. Defatting of the skin. Rash.

3. Composition / Information on Ingredients

Components	CAS #	Percent
Methylene Chloride	75-09-2	60 - 80
Butane	106-97-8	10 - 20
Propane	74-98-6	10 - 20
Proprietary Mixture	Proprietary	2.5 - 10
Toluene	108-88-3	2.5 - 10

Components	CAS #	Percent
Propylene Oxide	75-56-9	0.1 - 1
Other components below reportable levels		1 - 2.5

4. First Aid Measures

First aid procedures

Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
Skin contact	Remove and isolate contaminated clothing and shoes. Wash off with warm water and soap. Get medical attention if irritation develops and persists. For minor skin contact, avoid spreading material on unaffected skin.
Inhalation	If inhalation of gas/fume/vapor/dust/mist from the material is excessive (air concentration is greater than the TLV or health effects are noticed), immediately remove the affected person(s) to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician if symptoms develop or persist.
Ingestion	In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth thoroughly. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Notes to physician In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General advice Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. IF exposed or concerned: Get medical advice/attention. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation.

5. Fire Fighting Measures

Flammable properties Flammable by OSHA criteria. Heat may cause the containers to explode. Vapors may travel considerable distance to a source of ignition and flash back. Runoff to sewer may cause fire or explosion hazard.

Extinguishing media

Suitable extinguishing media Powder. Water. Carbon dioxide (CO₂).

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Protection of firefighters

Specific hazards arising from the chemical Fire may produce irritating, corrosive and/or toxic gases.

Protective equipment and precautions for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.

Fire fighting equipment/instructions In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental Release Measures

Personal precautions Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. For personal protection, see section 8 of the MSDS.

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not contaminate water.

Methods for containment Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Prevent entry into waterways, sewer, basements or confined areas.

Methods for cleaning up Should not be released into the environment. Stop the flow of material, if this is without risk. Isolate area until gas has dispersed. Following product recovery, flush area with water. For waste disposal, see section 13 of the MSDS.

7. Handling and Storage

Handling Vapors may form explosive mixtures with air. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not get this material in contact with eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin. Avoid prolonged exposure. Use only in area provided with appropriate exhaust ventilation. Wash thoroughly after handling.

Storage Contents under pressure. The pressure in sealed containers can increase under the influence of heat. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Keep away from food, drink and animal feedingstuffs. Keep in an area equipped with sprinklers. Use care in handling/storage. Store away from incompatible materials (see Section 10 of the MSDS). Level 1 Aerosol (NFPA 30B)

8. Exposure Controls / Personal Protection

Occupational exposure limits

ACGIH Biological Exposure Indices Components

Components	Type	Value
Methylene Chloride (CAS 75-09-2)	BEI	0.3 mg/l
Toluene (CAS 108-88-3)	BEI	0.3 mg/g 0.03 mg/l 0.02 mg/l

US. ACGIH Threshold Limit Values Components

Components	Type	Value
Methylene Chloride (CAS 75-09-2)	TWA	50 ppm
Propylene Oxide (CAS 75-56-9)	TWA	2 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) Components

Components	Type	Value
Methylene Chloride (CAS 75-09-2)	STEL	125 ppm
	TWA	25 ppm

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Components

Components	Type	Value
Propane (CAS 74-98-6)	PEL	1800 mg/m ³ 1000 ppm
Propylene Oxide (CAS 75-56-9)	PEL	240 mg/m ³ 100 ppm

US. OSHA Table Z-2 (29 CFR 1910.1000) Components

Components	Type	Value
Toluene (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye / face protection Do not get in eyes. Wear safety glasses with side shields (or goggles).

Skin protection	Avoid contact with the skin. Wear appropriate chemical resistant clothing. Chemical resistant gloves.
Respiratory protection	If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.
General hygiene considerations	When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical & Chemical Properties

Appearance	Not available.
Auto-ignition temperature	938.52 °F (503.62 °C) estimated
Boiling point	59.05 °F (15.03 °C) estimated
Color	Not available.
Flammability limits in air, upper, % by volume	51.9 % estimated
Flammability limits in air, lower, % by volume	12.2 % estimated
Flash point	-156.00 °F (-104.44 °C) Propellant estimated
Form	Aerosol.
Odor	Not available.
Odor threshold	Not available.
pH	Not available.
Physical state	Gas.
Solubility (water)	Not available.
Specific gravity	1.06 estimated
Vapor pressure	55 psig @68F estimated
Other data	
Heat of combustion	14.52 kJ/g estimated

10. Chemical Stability & Reactivity Information

Chemical stability	Risk of ignition.
Conditions to avoid	Heat, flames and sparks. Avoid temperatures exceeding the flash point.
Hazardous decomposition products	No hazardous decomposition products are known.
Possibility of hazardous reactions	Hazardous polymerization does not occur.

11. Toxicological Information

Toxicological data

Product	Species	Test Results
10 OZ 12PK CLEAR MAGIC (CAS Mixture)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	174.8078 ml/kg, estimated
<i>Inhalation</i>		
LC50	Guinea pig	64.2689 mg/l, 6 Hours, estimated
	Mouse	65955.8672 mg/l, 8 Hours, estimated
		4959.0874 mg/l, 24 Hours, estimated
		227.2867 mg/l, 7 Hours, estimated
		208.1676 mg/l, 2 Hours, estimated
		198.4666 mg/l, 6 Hours, estimated
	Rat	99181.75 mg/l, 4 Hours, estimated

Product	Species	Test Results
		8084.1792 mg/l, 15 Minutes, estimated
		355.7039 mg/l, 900 Days, estimated
		319.3251 mg/l, 2 Hours, estimated
		210.1886 mg/l, 6 Hours, estimated
		138.9238 mg/l/4h, estimated
LD50	Mouse	25579.668 mg/l, 7 Hours, estimated
<i>Oral</i>		
LD50	Rat	32.2341 g/kg, estimated
<i>Other</i>		
LD50	Mouse	355.0604 mg/kg, estimated
	Rabbit	477.2207 ml/kg, estimated
	Rat	12268.3994 mg/kg, estimated
Components	Species	Test Results
Butane (CAS 106-97-8)		
Acute		
<i>Inhalation</i>		
LC50	Mouse	680 mg/l, 2 Hours
	Rat	658 mg/l, 4 Hours
Methylene Chloride (CAS 75-09-2)		
Acute		
<i>Inhalation</i>		
LC50	Guinea pig	40.2 mg/l, 6 Hours
	Mouse	56.23 mg/l, 7 Hours
		51.5 mg/l, 2 Hours
		49.1 mg/l, 6 Hours
	Rat	2000 mg/l, 15 Minutes
		88 mg/l, 900 Days
		79 mg/l, 2 Hours
		52 mg/l, 6 Hours
LD50	Mouse	16000 mg/l, 7 Hours
<i>Oral</i>		
LD50	Rat	1600 mg/kg
<i>Other</i>		
LD50	Mouse	437 mg/kg
Propane (CAS 74-98-6)		
Acute		
<i>Inhalation</i>		
LC50	Rat	> 1442.847 mg/l, 15 Minutes
		658 mg/l/4h
Propylene Oxide (CAS 75-56-9)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	1245 mg/kg
<i>Inhalation</i>		
LC50	Mouse	1740 mg/l, 4 Hours
	Rat	4000 mg/l, 4 Hours

Components	Species	Test Results
<i>Oral</i>		
LD50	Guinea pig	660 mg/kg
	Rat	380 mg/kg
<i>Other</i>		
LD50	Mouse	175 mg/kg
	Rabbit	1.5 ml/kg
	Rat	150 mg/kg
Toluene (CAS 108-88-3)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	12124 mg/kg 14.1 ml/kg
<i>Inhalation</i>		
LC50	Mouse	5320 mg/l, 8 Hours 400 mg/l, 24 Hours
	Rat	26700 mg/l, If <1L: Consumer Commodity Hours 12200 mg/l, 2 Hours 8000 mg/l, 4 Hours
<i>Oral</i>		
LD50	Rat	2.6 g/kg
<i>Other</i>		
LD50	Mouse	59 mg/kg
	Rat	1332 mg/kg

* Estimates for product may be based on additional component data not shown.

Local effects	Components of the product may be absorbed into the body through the skin. Liver toxicity. Irritating to respiratory system. Irritating to skin. Contact may irritate or burn eyes.	
Chronic effects	Hazardous by OSHA criteria. Prolonged or repeated exposure may cause lung injury. Repeated absorption may cause disorder of central nervous system, liver, kidneys and blood. Prolonged exposure may cause chronic effects.	
Subchronic effects	Kidney injury may occur.	
Carcinogenicity	Hazardous by OSHA criteria. Risk of cancer cannot be excluded with prolonged exposure.	
ACGIH Carcinogens		
	Methylene Chloride (CAS 75-09-2)	A3 Confirmed animal carcinogen with unknown relevance to humans.
	Propylene Oxide (CAS 75-56-9)	A3 Confirmed animal carcinogen with unknown relevance to humans.
	Toluene (CAS 108-88-3)	A4 Not classifiable as a human carcinogen.
IARC Monographs. Overall Evaluation of Carcinogenicity		
	Methylene Chloride (CAS 75-09-2)	2B Possibly carcinogenic to humans.
	Propylene Oxide (CAS 75-56-9)	2B Possibly carcinogenic to humans.
	Toluene (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.
US NTP Report on Carcinogens: Anticipated carcinogen		
	Methylene Chloride (CAS 75-09-2)	Reasonably Anticipated to be a Human Carcinogen.
	Propylene Oxide (CAS 75-56-9)	Reasonably Anticipated to be a Human Carcinogen.
US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)		
	Methylene Chloride (CAS 75-09-2)	Potential cancer hazard.
Skin corrosion/irritation	Irritating to skin.	
Neurological effects	Hazardous by OSHA criteria.	
Further information	Symptoms may be delayed.	

12. Ecological Information

Ecotoxicological data

Product		Species	Test Results
10 OZ 12PK CLEAR MAGIC (CAS Mixture)			
Algae	IC50	Algae	696.5659 mg/L, 72 Hours, estimated
Crustacea	EC50	Daphnia	91.4925 mg/L, 48 Hours, estimated
Fish	LC50	Fish	154.2353 mg/L, 96 Hours, estimated
Components			
Methylene Chloride (CAS 75-09-2)			
Algae	IC50	Algae	500.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia	1689.5 mg/L, 48 Hours
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	1250 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	140.8 - 277.8 mg/l, 96 hours
Propylene Oxide (CAS 75-56-9)			
Crustacea	EC50	Daphnia	350 mg/L, 48 Hours
Toluene (CAS 108-88-3)			
Algae	IC50	Algae	433.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia	7.645 mg/L, 48 Hours
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon, silver salmon (Oncorhynchus kisutch)	8.11 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Ecotoxicity	Components of this product are hazardous to aquatic life.
Environmental effects	Harmful to aquatic organisms. An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Persistence and degradability	Not available.
Bioaccumulation / Accumulation	

Bioaccumulative potential

Octanol/water partition coefficient log Kow

Butane	2.89
Methylene Chloride	1.25
Propane	2.36
Propylene Oxide	0.03
Toluene	2.73

Partition coefficient

Butane	2.89
Methylene Chloride	1.25
Propane	2.36
Propylene Oxide	0.03
Toluene	2.73

13. Disposal Considerations

Waste codes	D001: Waste Flammable material with a flash point <140 F The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
--------------------	--

US RCRA Hazardous Waste U List: Reference

Methylene Chloride (CAS 75-09-2)	U080
Toluene (CAS 108-88-3)	U220

Disposal instructions

Contents under pressure. Do not puncture, incinerate or crush. Dispose of this material and its container to hazardous or special waste collection point. Incinerate the material under controlled conditions in an approved incinerator. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport Information**DOT****Basic shipping requirements:**

UN number UN1950
Proper shipping name Aerosols, flammable
Hazard class 2.1

Additional information:

Packaging exceptions 306
Packaging non bulk None
Packaging bulk None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2013, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/13 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA

UN number UN1950
UN proper shipping name Aerosols, flammable, containing substances in Division 6.1, Packing Group III
Transport hazard class(es) 2.1
Subsidiary class(es) 6.1(PGIII)
ERG code 10P
Packaging Exceptions LTD QTY

IMDG

UN number UN1950
UN proper shipping name AEROSOLS, MARINE POLLUTANT
Transport hazard class(es) 2.1
Subsidiary class(es) 6.1(PGIII)
Environmental hazards
Marine pollutant Yes
EmS F-D, S-U
Packaging Exceptions NOT a LTD QTY

DOT

IATA; IMDG



Marine pollutant



15. Regulatory Information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Toluene (CAS 108-88-3)	159 kg by weight
	50 gallons by volume
	6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Toluene (CAS 108-88-3)	35 % weight/volumn
------------------------	--------------------

DEA Exempt Chemical Mixtures Code Number

Toluene (CAS 108-88-3)	594
------------------------	-----

US EPCRA (SARA Title III) Section 302 - Extremely Hazardous Spill: Reportable quantity

Propylene Oxide (CAS 75-56-9)	100 lbs
-------------------------------	---------

US EPCRA (SARA Title III) Section 302 - Extremely Hazardous Substance: Threshold Planning Quantity

Propylene Oxide (CAS 75-56-9)	10000 lbs
-------------------------------	-----------

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration

Methylene Chloride (CAS 75-09-2)	0.1 %
Propylene Oxide (CAS 75-56-9)	0.1 %
Toluene (CAS 108-88-3)	1.0 %

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Methylene Chloride (CAS 75-09-2)	Listed.
Propylene Oxide (CAS 75-56-9)	Listed.
Toluene (CAS 108-88-3)	Listed.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA (Superfund) reportable quantity

Methylene Chloride: 1000
Toluene: 1000
Propylene Oxide: 100

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories	Immediate Hazard - Yes
	Delayed Hazard - Yes
	Fire Hazard - Yes
	Pressure Hazard - Yes
	Reactivity Hazard - No

Section 302 extremely hazardous substance	No
--	----

SARA 311/312 Hazardous chemical No

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

State regulations WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - New Jersey RTK - Substances: Listed substance

Butane (CAS 106-97-8)	Listed.
Methylene Chloride (CAS 75-09-2)	Listed.
Propane (CAS 74-98-6)	Listed.
Propylene Oxide (CAS 75-56-9)	Listed.
Toluene (CAS 108-88-3)	Listed.

US - Pennsylvania RTK - Hazardous Substances: Special hazard

Methylene Chloride (CAS 75-09-2)	Special hazard.
Propylene Oxide (CAS 75-56-9)	Special hazard.

US. Pennsylvania RTK - Hazardous Substances

Butane (CAS 106-97-8)	Listed.
Methylene Chloride (CAS 75-09-2)	Listed.
Propane (CAS 74-98-6)	Listed.
Propylene Oxide (CAS 75-56-9)	Listed.
Toluene (CAS 108-88-3)	Listed.

16. Other Information

Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

This data sheet contains changes from the previous version in section(s):

Product and Company Identification: Product Review
Regulatory Information: Canada